

DIRECTIONS FOR USE



Mr. Clean Graffiti Pasty Remover

Graffiti cleaner for smooth surfaces

Created on: 23-06-2005
Edited on: 18-01-2007

Features:

Mr. Clean Graffiti Pasty Remover especially serves to remove persistent graffiti from smooth surfaces indoors and outdoors.

Application:

Mr. Clean Graffiti Pasty Remover is applied onto the surface soiled with graffiti using a brush. With smooth surfaces, reaction time is 3 to 4 minutes; on porous surfaces, the product must be applied using a thick brush and strongly rubbed. When the graffiti has detached, wash the surface using plenty of water. Repeat the cleaning process, if necessary.

For after-treatment of the cleaned surfaces using high-pressure cleaning devices, we recommend water temperature from 70 °C to 90 °C and a pressure from 80 bar to 150 bar. The nozzle head should have an angle of 15 to 25 degrees, and the water flow should be 15 to 20 litres per minute. Removal of graffiti is possible at temperatures up to minus 5 °C.

Storage:

See safety data sheet

Preventive measures:

Danger warning: x_n - (harmful to health) see safety data sheet

Technical data:

Usage:	0,2-0,5 l/m ²	FEA number:	2656 0004
Other data:	see safety data sheet		

Additional notes:

Our products are based on extensive laboratory examinations and applications in practice. The information sheet on hand serves as an orientation only. We cannot guarantee to reach a particular final result. Users should carry out sufficient tests on the surfaces to be cleaned, and they are responsible for the result.