Application

The Drainprotector is a sealing mat that prevents released fluid chemicals from reaching drains, such as manhole covers, drainage grills and drainage channels.

The Spillbarrier (liquid barrier) provides a quick and versatile barrier for containing or diverting leaking liquids.

The products can be used for indoor and outdoor areas.

Store the Drainprotector/Spillbarrier so that it is protected against solar radiation and at room temperature.

Comply with current regulations when the Drainprotector/Spillbarrier has come into contact with hazardous chemicals.

Before use:

Unwind the Drainprotector or remove the protective film from the Spillbarrier.

Use:

If possible, remove all refuse from the area to be covered before installing the Drainprotector/Spillbarrier.

Place the Drainprotector over the drain and check that its dimensions are much bigger than the dimensions of the area to be covered. Lay the sticky side on the floor.

Install the Spillbarrier in such a way as to prevent any escaping liquid from spreading and above all from entering drains. Lay the sticky side on the floor.

After use:

A. In case of leaks with compatible liquids

Clean the Drainprotector/Spillbarrier with water and soap prior to storage.

Thoroughly dry the Drainprotector/Spillbarrier.

Roll up the Drainprotector and then store it.

Attach the protective film to the Spillbarrier and then store it.

B. In case of leaks with incompatible liquids

Dispose of in compliance with official regulations.

Characteristics

Drainprotector/Spillbarrier is composed of polyurethane, 100% elastomer.

Colour: yellow

Adhesive property: high performance

Chemical resistance

Resistant against oil and most of the water-based industrial chemicals. (See chemical compatibility list at www.raw-bindemittel.de).

Instructions for use and chemical compatibility list serve exclusively the purposes of user information. R.A.W. accepts no kind of liability. Testing is recommended prior to use.