

Technical Data Sheet



WIPE-AIRLAID

Universal Cleaning Cloth

Created on: 18. 12. 2009

Reviewed on: 22. 03. 2010

1. Technical data

Properties

Manufacturing method
Composition

Air laid
Cellulose 80%
Binding agent 20%
(ethylene vinyl
acetate/EVA)

- ✓ High capacity to absorb oil and water
- ✓ New fibres
- ✓ Smooth and soft
- ✓ Lint-free
- ✓ Does not scratch
- ✓ It can be used wet
- ✓ Biodegradation

Colour

White

Weight (40.3-90)

± 60 gr/m²

Thickness (30.4-89)

0.80 mm

Tensile strength dry (20.2-89)

0.42 kN/m (MD)

0.35 kN/m (CD)

Tensile strength wet (20.2-89)

0.22 kN/m (MD)

0.20 kN/m (CD)

Elongation dry (20.2-89)

14% (MD)

14% (XD)

Absorbing capacity (10.1-72)

510 gr/m²



2. Application areas



Hospitals




Laboratories



Cleaning



Industry



Microelectronics

3. Packaging alternatives



Folded in a
cardboard box



Perforated roll

4. Contact

RAW Handel und Beratungs GmbH
Grünstraße 5
D-79232 March-Hugstetten
Phone +49 (0) 7665 / 934 29 - 0
Fax +49 (0) 7665 / 934 29 - 25
info@raw-international.com
www.raw-international.com

This data is provided for informational purposes only and must not be regarded as binding. R.A.W. can not be held responsible for the use of this information. This data shall only be treated as typical features and not as binding specifications. Properties may change when used with substances which have not been mentioned. All information is subject to change without prior notice.